



کابل کواکسیال ساده

وزن تقریبی (Kg / Km)	قطر خارجی (mm)	تضعیف در MHz 100 (dB)	امپدانس (Ω)	جنس هادی	قطر نامی روی عایق (mm)	تعداد و قطر نامی هادی‌ها (mm)	نوع کابل
23	4	52	75	Copper	2.4	1x 0.4	2.5C - 2V
41	5.5	42	75	Copper	3	1x 0.5	3C - 2V
47	6.5	22	75	Copper	4.5	1x 1	4.5C - 2V
72	7.5	27	75	Copper	5	1x 0.8	5C - 2V
68	6.5	42	75	Copper	3	1x 0.5	3C - 2W
101	8.4	27	75	Copper	3	1x 0.8	5C - 2W
54	6.7	8.8	75	Copper	4.3	1x 1	RG - 6
128	9.5	8	50	Copper	6.4	7x 0.72	RG - 8
120	10.3	7.5	75	Tinned Copper	7.3	7x 0.4	RG - 11
38	5	17	50	Tinned Copper	2.95	19x 0.18	RG - 58
57	6.2	11.5	75	Copper	3.7	1x 0.60	RG - 59
165	10.3	6.8	50	Copper	7.25	7x 0.75	RG - 213
224	11	7.1	50	Copper	7.3	7x 0.77	RG - 214

